

# Wholesale Distributors of Quality Residential & Commercial Floor Coverings



### **Roll Program Product Collections**

Color Swatches, Product Specifications Maintenance & Warranty Information

2055 N. Airway Drive Baton Rouge, LA 70815 800-960-1209 Cust. Serv. 225-927-0120 Fax 5736 Blessey St. Harahan, LA 70123 800-960-1209 Cust. Serv. 504-734-7120 Fax 7028-A U.S. Hwy 49 N. Hattiesburg, MS 39402 800-960-1209 Cust. Serv. 601-261-9007 Fax Kevin's Warehouse 6130 Linwood Ave. Shreveport, LA 71106 Service Partner Xpress Global 9450 Maumelle Blvd. N. Little Rock AR 72113 Service Partner

# Canyon





# Canyon

# **Specification Sheet**



#### **PRODUCT INFORMATION**

Level of UseResidentialTotal Thickness105 gaugeWear Layer Thickness10 milsWear Layer TreatmentSuperGuard

Construction Heterogeneous Sheet Vinyl Finish Mechanically Embossed

#### **SIZE & PACKING**

Width 13'2" Standard Length 100 lineal ft.

Average Weight of Standard Roll 435 lbs

#### **TECHNICAL INFORMATION**

ASTM F1914 Residual Indentation .012

ASTM F137 Flexibility 10 mm Passes

ASTM F1514 Resistance to Heat Passes
ASTM F1515 Resistance to Light Passes
ASTM F925 Resistance to Chemicals Very Good

WARRANTY Limited 5 Year Residential Warranty



# Gladiator











Virginia 918

Phoenix 947

Titus 946









Babylon 933

Condor 992

Colorado 944

Toucan 936



Venturi 503



# **Gladiator**

# **Specification Sheet**



#### **PRODUCT INFORMATION**

Level of UseResidentialTotal Thickness125 gaugeWear Layer Thickness10 milsWear Layer TreatmentSuperGuard

Construction Heterogeneous Sheet Vinyl Finish Mechanically Embossed

#### **SIZE & PACKING**

Width 12'

Standard Length 75 lineal ft. Average Weight of Standard Roll 381.06 lbs

#### **TECHNICAL INFORMATION**

ASTM F1914 Residual Indentation .012

ASTM F137 Flexibility 6 mm Passes
ASTM F1514 Resistance to Heat Passes
ASTM F1515 Resistance to Light Passes
ASTM F925 Resistance to Chemicals Very Good

WARRANTY Limited 7 Year Warranty

**COLLECTION** Roll Program



IVC US, Inc. | 101 IVC Drive | Dalton, GA 30721 T 1-888-225-8287 | F 1-888-601-8544 www.ivcgroup.us

# Goliath

























Riviera 932

Vintage Oak 542

Cottage Oak 748



### Goliath

# **Specification Sheet**



#### **PRODUCT INFORMATION**

Level of UseResidentialTotal Thickness125 gaugeWear Layer Thickness12 milsWear Layer TreatmentSuperGuard

Construction Heterogeneous Sheet Vinyl Finish Mechanically Embossed

#### **SIZE & PACKING**

Width 13'2"
Standard Length 85 lineal ft.
Average Weight of Standard Roll 544 lbs

#### **TECHNICAL INFORMATION**

ASTM F1914 Residual Indentation .006

ASTM F137 Flexibility 10 mm Passes

ASTM F1514 Resistance to Heat Passes
ASTM F1515 Resistance to Light Passes
ASTM F925 Resistance to Chemicals Very Good

WARRANTY Limited 10 Year Residential Warranty



# Selecta



Elba 933



Rocky 982

# Selecta

# **Specification Sheet**



#### **PRODUCT INFORMATION**

Level of UseResidentialTotal Thickness55 gaugeWear Layer Thickness5 milsWear Layer TreatmentQuickclean

Construction Heterogeneous Sheet Vinyl Finish Mechanically Embossed

#### **SIZE & PACKING**

Width 13'2"

Standard Length 120 lineal ft.
Average Weight of Standard Roll 413 lbs

#### **TECHNICAL INFORMATION**

ASTM F1914 Residual Indentation .006


ASTM F137 Flexibility 10 mm Passes

ASTM F1514 Resistance to Heat Passes
ASTM F1515 Resistance to Light Passes
ASTM F925 Resistance to Chemicals Very Good

WARRANTY Limited 1 Year Residential Warranty









# **Step Up**

# **Specification Sheet**



#### **PRODUCT INFORMATION**

Level of UseResidentialTotal Thickness90 gaugeWear Layer Thickness8 milsWear Layer TreatmentQuickclean

Construction Heterogeneous Sheet Vinyl Finish Mechanically Embossed

#### **SIZE & PACKING**

Width 13'2"
Standard Length 100 lineal ft.
Average Weight of Standard Roll 396 lbs

#### **TECHNICAL INFORMATION**

ASTM F1914 Residual Indentation .010

ASTM F137 Flexibility 10 mm Passes

ASTM F1514 Resistance to Heat Passes
ASTM F1515 Resistance to Light Passes
ASTM F925 Resistance to Chemicals Very Good

WARRANTY Limited 3 Year Residential Warranty







#### **CARE & MAINTENANCE**

Your *FLEXITEC* cushioned vinyl flooring will provide years of carefree use. You will find that it is not only beautiful, but durable. It is also much easier to maintain than most other flooring products because of the tough protective finish and moisture resistance.

It only takes a few simple care and maintenance steps to keep your floor looking new for years to come.

#### To keep your floor clean and beautiful:

- Sweep the floor with a soft bristle broom to remove loose dirt.
- Wash the floor with a non-abrasive floor cleaner.
- For everyday maintenance, a mop moistened with warm water will suffice.
- Do not use soap based detergents.
- Do not use abrasive or mop and shine products.
- Do not wax the floor.
- Do not use ammonia or bleaches.
- Do not use a vacuum cleaner with a rotating beater bar.
- Do not use a steam mop.
- Make sure furniture legs have large surface, non-staining floor protectors. Replace small, narrow metal or domeshaped glides with smooth, flat glides that are in flat contact with the floor.
- Heavy furniture or appliances that are not moved often should be equipped with flat, non-staining composition furniture casters or cups of appropriate size.

Always read the cautionary information on all cleaners prior to use.

IMPORTANT: NEVER push, pull or drag heavy furniture or other items across the floor. When moving furniture or heavy items, always *lift and carry* the items, if possible. Otherwise, use furniture sliders available at most hardware, home improvement and discount stores.







### **HOW TO TREAT STAINS, SPILLS AND SCUFFS**

Follow the remedies in order. Unless instructed otherwise, use a clean, **white** cloth or towel with the recommended liquids. Always rinse the affected area with clean water after treatment.

#### **Stains and Spills**

- · Acids, alkalis
- Blood
- Catsup, Mustard
- Cleaners, Strong Soaps
- Dye, Dye Markings
- Food, Candy
- Fruit and Fruit Juices
- Grass
- Iodine, Mercurochrome
- Rust
- Urine, Excrement

#### **Paint and Solvent Spills**

- · Dry Cleaning Fluids
- Lacquer
- Latex Paint
- Nail Polish
- Solvents
- Oil-Based Paints
- Wood Stains
- Varnish

#### Substances that won't wipe up

- Adhesives
- Asphalt
- Chewing Gum
- Oil
- Grease
- Candle Wax
- Tar

#### **Scuffs and Smudges**

- Rubber Heel Marks
- Shoe PolishScuffs
- Smudges



#### Remedy

- · Scrub area with a vinyl cleaner full strength
- Rub the area with a 10 to 1 dilution of water to liquid bleach
- · Rub the area with isopropyl alcohol
- If rust stain does not respond, use lemon juice or a cream of tarter solution

#### Remedy

- If substance is dry, gently peel it from the floor.
   (Avoid sharp instruments that could scratch the floor.)
- Scrub area with non-abrasive cleaner suitable for vinyl flooring
- Rub lightly with odorless mineral spirits or paint thinner

#### Remedy

- · Carefully remove excess with a dull kitchen knife or fingernail
- · Scrub area with non-abrasive cleaner suitable for vinyl flooring
- Rub lightly with odorless mineral spirits, isopropyl alcohol or lighter fluid

#### Remedy

- Rub the scuff with fingertip, rubber will come right off (friction from the rubbing will remove rubber)
- · Scrub area with non-abrasive cleaner suitable for vinyl flooring
- · Rub lightly with isopropyl alcohol or lighter fluid

Note: Most grocery stores, discount stores, mass merchandisers and home centers carry cleaners suitable for vinyl flooring.

Caution: Isopropyl alcohol, lighter fluid, odorless mineral spirits and paint thinner are flammable solvents. Carefully read and follow cautionary information on label. Keep traffic off treated area for 30 minutes.





This warranty only extends to the original end user and is not transferable.

#### LIMITED WARRANTY PERIODS

1 Year: SELECTA
3 Years: STEP-UP
5 Years: CANYON
7 Years: GLADIATOR
10 Years: GOLIATH

**IVC US** warrants that first quality products which are used for recommended Residential purposes will perform properly for the stated warranty period when installed in accordance with IVC US installation instructions over approved substrates and underlayments and using the recommended adhesives and seam sealers. The warranty period, when valid, begins on the date of the original installation. This warranty only extends to the original purchaser and is non-transferable.

#### This warranty is only valid for Residential use.

Residential use means: use in environments (which <u>do not</u> have light or heavy commercial traffic) including all areas of single and multi-family housing. (Please note warranty exclusions with respect to caster and rolling loads due to the unusual characteristics of this type of wheel traffic.) If there is a question as to the type of use that is considered "Residential" please contact your IVC US representative prior to purchase and installation.

HOUSING	Single-Family Housing	All interior areas, excluding garages and solariums
MULTI-FAMILY HOUSING	Multi-Family Housing	Bathrooms, Kitchens

1 Year: SELECTA 3 Years: STEP-UP 5 Years: CANYON

FOR THE DESIGNATED WARRANTY PERIOD WHEN PROPERLY INSTALLED\*\* YOUR **IVC US** FLOORING WILL NOT:

- Contain manufacturing defects
- Contract, expand, curl, crack, rip, tear, or gouge from normal household use with proper maintenance\*
- Discolor from moisture
- Be affected by mold, mildew and/or alkaline when properly installed according to the IVC US Installation Guidelines\*\*





7 Years: GLADIATOR 10 Years: GOLIATH

FOR THE DESIGNATED WARRANTY PERIOD WHEN PROPERLY INSTALLED \*\* YOUR IVC US FLOORING WILL NOT:

- Contain manufacturing defects
- Contract, expand, curl, crack, rip, tear, or gouge from normal household use with proper maintenance\*
- Discolor from moisture
- Be affected by mold, mildew and/or alkaline when properly installed according to the IVC US Installation Guidelines\*\*
- Permanently stain from common cleaning products made for vinyl flooring.
- Permanently stain or yellow from foot traffic \*\*\*
- Permanently scuff from shoe soles
- Wear-through the wear layer under normal conditions with proper maintenance\*\*\*\*

#### **ADDITIONAL INFORMATION:**

- The conditions above will be warranted as long as the flooring is installed in an environment that maintains a temperature range of 55° to 85° F. Any of the above conditions will not be covered if caused by job site environmental conditions in new construction or renovation work.
- IVC US floorings receive extensive testing as well as visual examinations in an attempt to assure your shipped floor is always first quality. The installer / end user are responsible to confirm the received material is free of any obvious visible conditions that may be detrimental to the appearance and performance of the product. Inspection of material <u>prior to installation</u> for any imperfections or manufacturing related defects is required.
- Minor color, shade and or texture variations are normal, any variances between actual material, product samples and/or brochures should be addressed with your retailer prior to the installation. If the retailer determines the condition, "unacceptable" the manufacturer should be informed immediately.
- Support furniture with wide, weight-bearing, smooth non-staining floor protectors. The protectors should be at least one (1) inch in diameter, made of clear smooth hard plastic, and rest flat on the floor. Non-staining felt protectors are also acceptable provided they are a minimum one (1) inch in diameter. Felt pads should be inspected and maintained with respect to the amount of foot traffic to remove imbedded material to avoid abrasion. Make sure any metal protectors are rust-proof. Replace narrow dome furniture rests with the appropriate width, weight-bearing flooring protectors. The heavier the item the wider the floor protector should be.
- Chair pads designed for hard surface floors are required under all chairs and stools with casters.

#### WHAT IS NOT COVERED BY THIS WARRANTY

- Product sold by the manufacturer as other than "first quality."
- Loose lay installations of more than 25 square yards.
- **IMPROPER INSTALLATION:** Material installed not in accordance with **IVC US** recommended installation guidelines, including any and all problems caused by the used of non-recommended adhesive or seam sealer, underlayment and/or preparation of the substrate are not warranted. Installation errors are not manufacturing related conditions. You should discuss them with your installer. **IVC** does not warrant installer workmanship.
- **IVC US** will not pay labor costs to repair or replace material with visible conditions that were apparent before installation.





- Improper maintenance which results in loss of gloss or build-up of a dulling film.
- Damage resulting from neglect or misuse of strong detergents, chemicals, corrosives "including but not limited to" stains from paints, dyes, mats, fertilizers or other similar materials.
- Damage caused by moving appliances or heavy furniture without protecting the floor. (Always protect floor by using plywood or hard board runways when moving heavy objects, also when using an appliance dolly, heavy objects equipped with wheels or rollers including two and four wheel carts etc.)
- Damage resulting from accidents, casualty events, abuse or improper usage. Accidents, abuse and improper usage are defined as, but are not limited to damage caused by casters\*\*\*\*\* on furniture, rotating beater bars on vacuum cleaners, burns, cuts, impact from heavy and sharp objects, narrow or spike heels, cleats etc. as well as damage resulting from unprotected furniture legs.
- Damage caused by rolling loads or wheel chairs (motorized and non-motorized).
- Damage caused by steam mops, appliance or plumbing leaks. Accidents, abuse and improper use (including pet related damage).
- Fading, discoloration, or other damage due to excessive temperatures or sunlight. Radiant heat must not exceed 86 ° F.
- Problems or damage due to excessive moisture or hydrostatic pressure from the subfloor including pH levels outside the IVC US installation guidelines.\*\*
- Discoloration caused by use of latex or rubber-backed floor mats. Note some synthetic backed carpets contain latex in the manufacturing process that may discolor your vinyl.
- Discoloration caused by asphalt walk off traffic.
- Damage caused by remodel or construction related activities.
- Problems or damage due to excessive moisture or hydrostatic pressure from the subfloor including pH levels outside the IVC US Installation Guidelines.
- Installation of residential product in a commercial environment. IVC US recommends installation of commercially warranted product only in commercial settings.

#### **WARRANTY REMEDY**

If your **IVC US** floor fails to perform as stated in the applicable Residential Limited Warranty, **IVC US** will supply new **IVC** material of the same color, design or grade if available. If unavailable or discontinued, **IVC US** reserves the right to select and supply similar **IVC** material.

- If your floor was installed by a professional flooring contractor, **IVC US** will also credit back reasonable cost for the professional labor to install your replacement floor. Please note a detailed receipt is required for the cost of the original installation.
- If IVC US authorizes repairs or replacement of a section as a result of a warranty claim, you will be required to clear any items placed over the affected area subsequent to the original installation. IVC US will not credit or reimburse cost associated with the removal of those items.
- Warranty coverage for a replacement floor will be limited to the remaining portion of the original warranty.
- **IVC US** will not participate in labor reimbursement after year one.
- Labor reimbursement will not be considered for installations not adhering to the IVC US installation guidelines.\*\*





#### **CONSEQUENTIAL OR INCIDENTAL DAMAGES**

**IVC US** excludes and will not pay consequential or incidental damages under these limited warranties. By this we mean that IVC US will not credit or pay for any loss, expense, or damage other than to the flooring itself that may result from a manufacturing related defects in the flooring. Some examples of consequential or incidental damages are: replacement of subfloors, trim moldings, disconnecting / reconnecting appliances or fixtures as well as moving of furniture.

Note: If your floor is replaced because of discoloration or "bottom up staining", mold or mildew growth or asphalt / non-asphalt tracking, the replacement floor will not be warranted against future discoloration or staining.

#### Recommended adhesive and seam sealer:

**IVC FLEX-TECH** Pressure Sensitive Adhesive

IVC FLEX-SEAM Premium Seam Bond

THERE ARE NO WARRANTIES BEYOND THIS EXPRESSED WARRANTY. ALL OTHER WARRANTIES INCLUDING IMPLIED WARRANTIES, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, ARE EXCLUDED. PLEASE NOTE: SOME STATES AND PROVIDENCES DO NOT ALLOW EXCLUSIONS OR LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE LIMITATIONS OR EXCLUSIONS MAY NOT APPLY TO YOU.

#### **HOW TO REPORT A CLAIM**

If you find a manufacturing related condition covered by any of the limited warranties described previously, promptly notify the retailer or contractor who sold you the floor covering material. The retailer or contractor will file a claim directly with **IVC US**.

<sup>\*</sup>Normal household use is defined as common daily activities in the home, excluding pets.

<sup>\*\*</sup> The installation manual is reviewed on a regular basis, and floors must be installed according to the recommendations that are current and available at the time of installation.

<sup>\*\*\*</sup> IVC US recommends non-asphalt sealers.

<sup>\*\*\*\*</sup> Wear-through is defined as complete loss of the wear layer so that the printed pattern or design is altered. Gloss reduction is not considered wear and is not covered by this warranty.

<sup>\*\*\*\*\*</sup> IVC US does not recommend the use of casters on any flooring without appropriate chair pads.